

## USZCZELKI CAMLOCK cz.1

### Uszczelka standardowa - płaska

DN	Cal	Materiał				Ø zewn. +/- 0,2 mm	Ø wewn. +/- 0,2 mm	Wysokość +/- 0,2
		NBR	EPDM	Viton	Hypalon			
15	½"	CAM15N	CAM15E	CAM15V	CAM15H	26,5	17,5	4,0
20	¾"	CAM20N	CAM20E	CAM20V	CAM20H	32,0	22,0	5,5
25	1"	CAM25N	CAM25E	CAM25V	CAM25H	40,0	27,0	6,4
32	1 ¼"	CAM32N	CAM32E	CAM32V	CAM32H	50,0	35,0	6,4
40	1 ½"	CAM40N	CAM40E	CAM40V	CAM40H	56,0	41,0	6,4
50	2"	CAM50N	CAM50E	CAM50V	CAM50H	67,0	51,0	6,4
65	2 ½"	CAM65N	CAM65E	CAM65V	CAM65H	80,0	60,0	6,4
80	3"	CAM80N	CAM80E	CAM80V	CAM80H	95,0	76,0	6,4
100	4"	CAM100N	CAM100E	CAM100V	CAM100H	124,0	102,0	6,4
125	5"	CAM125N	CAM125E	CAM125V	CAM125H	150,5	124,0	6,4
150	6"	CAM150N	CAM150E	CAM150V	CAM150H	180,0	153,0	6,4



### Uszczelka powlekana Viton / Silikon - zamknięta

Index	DN	Cal	Ø zewn. +/- 0,2 mm	Ø wewn. +/- 0,2 mm	Wysokość +/- 0,2	Waga
CAMPO15VS	15	½"	26,6	17,5	4,0	0,002
CAMPO20VS	20	¾"	35,0	22,2	5,5	0,004
CAMPO25VS	25	1"	39,7	27,0	6,5	0,006
CAMPO32VS	32	1 ¼"	49,2	34,5	6,5	0,010
CAMPO40VS	40	1 ½"	55,5	41,3	6,5	0,012
CAMPO50VS	50	2"	66,7	50,8	6,5	0,014
CAMPO65VS	65	2 ½"	79,4	60,3	6,5	0,018
CAMPO80VS	80	3"	95,5	76,2	6,5	0,022



### Uszczelka kopertowa PTFE / EPDM - otwarta

Index	DN	Cal	Ø zewn. +/- 0,2 mm	Ø wewn. +/- 0,2 mm	Wysokość +/- 0,2	Waga
CAMKO15PE	15	½"	26,2	17,5	4,0	0,002
CAMKO20PE	20	¾"	35,3	21,2	5,5	0,004
CAMKO25PE	25	1"	39,0	23,0	6,4	0,006
CAMKO32PE	32	1 ¼"	49,5	32,4	6,4	0,009
CAMKO40PE	40	1 ½"	55,2	35,2	6,4	0,012
CAMKO50PE	50	2"	66,0	47,0	6,4	0,014
CAMKO65PE	65	2 ½"	79,0	58,5	6,4	0,020
CAMKO80PE	80	3"	94,5	76,3	6,4	0,022
CAMKO100PE	100	4"	124,0	102,0	6,4	0,032





## USZCZELKI CAMLOCK cz.2

### Uszczelka kopertowa PTFE / Viton - otwarta

Index	DN	Cal	Ø zewn. +/- 0,2 mm	Ø wewn. +/- 0,2 mm	Wysokość +/- 0,2	Waga
CAMKO15PV	15	1/2"	26,2	17,5	4,0	0,002
CAMKO20PV	20	3/4"	35,3	21,2	5,5	0,004
CAMKO25PV	25	1"	39,0	23,0	6,4	0,006
CAMKO32PV	32	1 1/4"	49,5	32,4	6,4	0,009
CAMKO40PV	40	1 1/2"	55,2	35,2	6,4	0,012
CAMKO50PV	50	2"	66,0	47,0	6,4	0,014
CAMKO65PV	65	2 1/2"	79,0	58,5	6,4	0,020
CAMKO80PV	80	3"	94,5	76,3	6,4	0,022
CAMKO100PV	100	4"	124,0	102,0	6,4	0,032



### Uszczelka powlekana PTFE / Viton - zamknięta

Index	DN	Cal	Ø zewn. +/- 0,2 mm	Ø wewn. +/- 0,2 mm	Wysokość +/- 0,2	Waga
CAMPO15PV	15	1/2"	26,5	13,5	4,5	0,002
CAMPO20PV	20	3/4"	35,0	18,0	5,7	0,004
CAMPO25PV	25	1"	41,8	23,5	6,5	0,006
CAMPO32PV	32	1 1/4"	48,0	30,0	6,5	0,009
CAMPO40PV	40	1 1/2"	56,0	35,5	6,5	0,010
CAMPO50PV	50	2"	57,0	46,5	6,5	0,012
CAMPO65PV	65	2 1/2"	81,5	60,0	6,5	0,016
CAMPO80PV	80	3"	94,0	76,0	6,5	0,018
CAMPO100PV	100	4"	122,5	100,5	6,5	0,024



### Uszczelka GWINTU PTFE

Index	DN	Cal	Ø zewn. +/- 0,2 mm	Ø wewn. +/- 0,2 mm	Wysokość +/- 0,2	Waga
CAMPO20PV	20	3/4"	26,0	19,0	1,5	0,001
CAMPO25PV	25	1"	33,0	24,0	2,0	0,002
CAMPO32PV	32	1 1/4"	42,0	33,0	2,0	0,002
CAMPO40PV	40	1 1/2"	48,0	39,0	2,0	0,003
CAMPO50PV	50	2"	60,0	49,0	2,0	0,004
CAMPO65PV	65	2 1/2"	76,0	63,0	2,5	0,006
CAMPO80PV	80	3"	88,0	77,0	3,0	0,010
CAMPO100PV	100	4"	114,0	100,0	3,0	0,015



### Uszczelka GWINTU PU

Index	DN	Cal	Ø zewn. +/- 0,2 mm	Ø wewn. +/- 0,2 mm	Wysokość +/- 0,2	Waga
CAMPO20PV	20	3/4"	26,0	19,0	1,5	0,001
CAMPO25PV	25	1"	33,0	24,0	2,0	0,002
CAMPO32PV	32	1 1/4"	42,0	33,0	2,0	0,002
CAMPO40PV	40	1 1/2"	48,0	39,0	2,0	0,003
CAMPO50PV	50	2"	60,0	49,0	2,0	0,004
CAMPO65PV	65	2 1/2"	76,0	63,0	2,5	0,006
CAMPO80PV	80	3"	88,0	77,0	3,0	0,010
CAMPO100PV	100	4"	114,0	100,0	3,0	0,015

